

<b>Brand:</b>	<b>HONLIX</b>
<b>P/N:</b>	HLK-701-1
<b>MOQ:</b>	500PCS/PER
<b>Place of Origin:</b>	Kunshan City,China
<b>Delivery Time:</b>	1 week
<b>Start Port:</b>	Shanghai
<b>General features:</b>	
Product Name	GB/T V2L Discharge adapter female <b>Pile end 1KΩ</b> New national standard five holes GB/T 20234.1/2-2015
Product Spec	7 PIN Female
Connector locking system	Yes
Degree of protection	IP55
Ambient temperature(operation)	-25°C~+85°C
Customs tariff number	8536901900
Environmental compliance	RoHs, Reach
<b>Electrical parameters:</b>	
Rated voltage	250V
Rated current(25°C)	10A~16A (2500W~4000W)
Withstand voltage	500V
Contact resistance	≤10mΩ
Insulation resistance	≥20MΩ
<b>Mechanical performance:</b>	
Mechanical operation	≤5000 mating cycles
Insertion force	≤100N
Pull out force	≤100N
Wiring range	2.5mm <sup>2</sup> /6mm <sup>2</sup>
<b>Application Area</b>	
Use of discharge adapter connectors for electric motorcycles, electric vehicles, and RVs	