

# **HONLIX**

充电桩 & 放电枪  
Charging Pile & Discharge Gun



# 公司简介

## Company Profile

**HONLIX**

弘林科电工科技（昆山）有限公司成立于2016年，坐落于中国昆山市张浦镇德国工业园区内，工厂位于江苏昆山和河南南阳。公司专注于新能源电动自行车/滑板车/平衡车，电动摩托车，电动汽车整体连接解决方案，为客户提供一站式解决方案。

公司拥有专业的研发团队+销售团队+制造团队+品保团队，可提供整套连接器，线束组件的设计方案及选型建议，为客户提供优质的产品和快速的交期，具有良好的市场竞争力，得到广大客户的支持和信赖。

公司已经通过ISO9001:2015质量管理体系认证，IATF16949：2016正在规划中，拥有国家专利20余项，产品认证已通过ROHS REACH CE CCC等。

HONLIX Electrician Technology (Kunshan) Co., Ltd. was established in 2016 and is located in the German Industrial Park, Zhangpu Town, Kunshan City, China. The factories are located in Kunshan, Jiangsu and Nanyang, Henan. The company focuses on the overall connection solutions of new energy electric bicycles/scooters/balance vehicles, electric motorcycles, and electric vehicles, providing customers with one-stop solutions.

The company has a professional R & D team + sales team + manufacturing team + quality assurance team, can provide a complete set of connectors, wiring harness components design solutions and selection suggestions, to provide customers with high-quality products and fast delivery, with good market competition We have won the support and trust of our customers.

The company has passed ISO9001:2015 quality management system certification, IATF16949:2016 is under planning, has more than 20 national patents, and product certification has passed ROHS, REACH, CE, CCC, etc.

工厂照片  
KS/HN Factory



**KUN SHAN Factory**



**HE NAN Factory**

# 资质证书 Company Certificate

# HONLIX



Business License



Letter of Credit



Chinese/English Trademark Certificate



ISO9001:2015



CCC Certificate



ROHS Certificate



CE Certificate



More than 20 Patent Certificates in China 5



# 目 录

## CONTENS

**HONLIX**

A. GB/EU/US Discharge Gun-----	7-13
B. European Standard Twin Guns-----	14
C. GB TYPE 2 3.5KW AC-----	15
D. GB/EU/US TYPE 2 3.5KW AC Basic Style -----	16
E. GB/EU/US TYPE 2 3.5KW/7KW AC Luxury Version -----	17~20
F. GB/EU/US 7KW AC Single Player Version Charging Station-----	21
G. GB/EU/US 7KW AC WIFI&4G Version Charging Station-----	22



**HLK-701**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-701
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	National Standard Discharge Gun
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A / 32A
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5mm2 EV 3*6.0mm2
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-701-1**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-701-1
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	National Standard Discharge Gun <b>Pile End</b>
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	N/A
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	





**HLK-701-2**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-701-2
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	National Standard Discharge Gun <b>Car End</b>
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	N/A
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-702**  
**[URL Download](#)**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-702
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	EU Standard Discharge Gun
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A / 32A
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5mm2 EV 3*6.0mm2
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-702-1**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-702-1
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	EU Discharge Gun <b>Pile End</b>
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	N/A
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-702-2**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-702-2
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	EU Discharge Gun <b>Car End</b>
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	N/A
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-703**  
**[URL Download](#)**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-703
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	US Standard Discharge Gun
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A / 32A
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥ 500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5mm2 EV 3*6.0mm2
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-704**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-704
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	UK Standard Discharge Gun
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A / 32A
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥ 500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5mm2 EV 3*6.0mm2
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-705**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-705
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	模式二国标控制盒 3.5kw 16A 220V Mode 2 National Standard Control Box 3.5kw 16A 220V
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A 220V 3.5kw
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5mm2 EV 3*6.0mm2
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-706 HLK-707 HLK-708**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-706 707 708
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	China/EU/US 16A AC Charging Model-2
Product Spec 规格型号	9PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A 3.5KW
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5+2*0.75
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	





**HLK-709 HLK-710 HLK-711**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-709 710 711
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	China/EU/US 16A AC Charging Model-2
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A 3.5KW
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5+2*0.75
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-712 HLK-713 HLK-714**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-712 713 714
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	China/EU/US 16A 3.5kw AC Charging <b>2.8 inch display screen</b>
Product Spec 规格型号	7 PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	16A 3.5KW
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5+2*0.75
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-715 HLK-716 HLK-717**  
**URL Download**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-709 710 711
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	China/EU/US 32A 7KW AC Charging Model-2
Product Spec 规格型号	7 PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	32A 7KW
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5+2*0.75
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



HLK-718 HLK-719 HLK-720  
URL Download

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-712 713 714
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	China/EU/US 32A 7kw AC Charging <b>2.8 inch display screen</b>
Product Spec 规格型号	7 PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	32A 7KW
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5+2*0.75
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-721 HLK-722 HLK-723**

**URL Download**

**GB/EU/US Single vision**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-721/722/723
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	GB/EU/US 7kw AC Single version
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	32A 7KW
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5+2*0.75
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	



**HLK-724 HLK-725 HLK-726**

**URL Download**

**4 "LCD Screen APP Version Bluetooth WIFI**

Brand: 品牌:	HONLIX 弘林科
P/N: 料号	HLK-724/725/726
MOQ: 起订量	500PCS/Order 500条/次
Place of Origin: 产地	Kunshan City,China 中国昆山
Delivery Time: 交货周期	1 week 1周
Export Port: 发出港口	Shanghai 上海
<b>General features: 一般特性:</b>	
Product Name 产品名称	GB/EU/US 7kw AC 4G&WiFi 4 "LCD screen
Product Spec 规格型号	7PIN Male
Connector locking system 互锁	Interlock
Ingree of protection ratings 防护等级	IP55
Ambient temperature(operation) 耐温	-25°C~+85°C
Customs tariff number 海关编码	8536901900
Environmental compliance 环保等级	RoHs, Reach
<b>Electrical parameters: 电气参数:</b>	
Rated voltage 电压等级	1000V
Rated current(25°C) 额定工作电流	32A 7KW
Withstand voltage 耐电压	AC 3000V 250V/50HZ/1Min PASS
Contact resistance 接触电阻	≥0.5mΩ Max
Insulation resistance 绝缘电阻	≥500MΩ/DC500V
<b>Mechanical performance: 机械参数:</b>	
Mechanical life 插拔寿命	≤10000 mating cycles
Insertion force 插入力	≤140N
Pull out force 拔出力	≥70N
Insertion force 配线范围	EV 3*2.5+2*0.75
<b>Application Area: 应用领域</b>	
Charger for Motorcycles and electric vehicles 电动汽车, 电动摩托车等领域	

**HONLIX**

**Thanks!**

[www.honlix.com](http://www.honlix.com)